

GREY LIGHT KEDER

TECHNICAL DATA SHEET

FABRIC

CHARACTERISTICS	SPECIFICATION	METHOD
TEXTILE SUPPORT	POLYESTER HT 1100 dtex	
CONSTRUCTION	7x7	
COATING	PVC 1 SIDE MATT FINISH	
COLOUR	GREY	
OPACITY	TRANSLUCENT	
TOTAL MASS	410 gr/m ²	EN ISO 2286-2
FABRIC MASS	155 gr/m ²	
THICKNESS	0,41 mm	
BREAKING LOAD ALONG	240 daN/5cm	EN ISO 1421
BREAKING LOAD ACROSS	200 daN/5cm	EN ISO 1421
BREAKING EXTENSION ALONG	18%	EN ISO 1421
BREAKING EXTENSION ACROSS	22%	EN ISO 1421
TEAR STRENGTH ALONG	25 daN	EN ISO 4674-1B
TEAR STRENGTH ACROSS	20 daN	EN ISO 4674-1B
COATING ADHESION	min. 7 daN/5cm	EN ISO 2411
TEMPERATURE OF RESISTANCE	-25 / + 80 °C	

INTERNAL CORD

MASSIVE CORD PVC EXTRUDED
DIAMETERS 3,2 to 7,5 mm

NOTE: The technical information has been facilitated by our suppliers, and is based on the results average of every manufacture

These cannot be considered legally binding